

The listing of claims will replace all prior versions, and listings, of claims in the application:

**Listing of Claims:**

1. (Currently Amended) A semiconductor device comprising:  
stacked semiconductor elements each having at least one thin film transistor;  
a resin film formed between the stacked semiconductor elements; ~~[[and]]~~  
~~at least one of a light emitting element and a light receiving element~~ electrically  
connected to ~~[[each]]~~ one of the stacked semiconductor elements, and  
a light receiving element electrically connected to another one of the stacked  
semiconductor elements.

wherein a signal is transmitted and received between the stacked semiconductor elements by using the light emitting element and the light receiving element.

2. (Currently Amended) A semiconductor device comprising:  
stacked semiconductor elements each having at least one thin film transistor;  
a resin film formed between the stacked semiconductor elements;  
a metal oxide partially formed between the stacked semiconductor elements; and  
~~at least one of a light emitting element and a light receiving element~~ electrically  
connected to ~~[[each]]~~ one of the stacked semiconductor elements, and  
a light receiving element electrically connected to another one of the stacked  
semiconductor elements.

wherein a signal is transmitted and received between the stacked semiconductor elements by using the light emitting element and the light receiving element.

3. (Previously Presented) A semiconductor device comprising:  
stacked semiconductor elements each having at least one thin film transistor;

a resin film formed between the stacked semiconductor elements;

a light emitting element electrically connected to one of the stacked semiconductor elements; and

a light receiving element electrically connected to another one of the stacked semiconductor elements,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element.

4. (Previously Presented) A semiconductor device comprising:

stacked semiconductor elements each having at least one thin film transistor;

a resin film formed between the stacked semiconductor elements;

a metal oxide partially formed between the stacked semiconductor elements;

a light emitting element electrically connected to one of the stacked semiconductor elements; and

a light receiving element electrically connected to another one of the stacked semiconductor elements,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element.

5. (Previously Presented) A semiconductor device comprising:

semiconductor elements each having at least one thin film transistor stacked by transferring a semiconductor element formed over a different substrate;

a resin film formed between the stacked semiconductor elements;

a light emitting element electrically connected to one of the stacked semiconductor elements; and

a light receiving element electrically connected to another one of the stacked semiconductor elements,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element.

6. (Previously Presented) A semiconductor device comprising:  
semiconductor elements each having at least one thin film transistor stacked by transferring a semiconductor element formed over a different substrate;

a resin film formed between the stacked semiconductor elements;

a metal oxide partially formed between the stacked semiconductor elements;

a light emitting element electrically connected to one of the stacked semiconductor elements; and

a light receiving element electrically connected to another one of the stacked semiconductor elements,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element.

7. (Previously Presented) A semiconductor device formed by detaching a plurality of semiconductor elements each formed over a plurality of substrates and by stacking the detached plurality of semiconductor elements over an element substrate, comprising:

a resin film formed between the plurality of stacked semiconductor elements;

a light emitting element electrically connected to one of the plurality of semiconductor elements; and

a light receiving element electrically connected to another one of the plurality of semiconductor elements,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element,

wherein each of the semiconductor elements has at least one thin film transistor.

8. (Previously Presented) A semiconductor device formed by detaching a plurality of semiconductor elements each formed over a plurality of substrates and by stacking the detached plurality of semiconductor elements over an element substrate, comprising:

a resin film formed between the plurality of stacked semiconductor elements;

a metal oxide partially formed between the plurality of stacked semiconductor elements;

a light emitting element electrically connected to one of the plurality of semiconductor elements; and

a light receiving element electrically connected to another one of the plurality of semiconductor elements,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element,

wherein each of the semiconductor elements has at least one thin film transistor.

9. (Previously Presented) A semiconductor device comprising:

a plurality of stacked thin film integrated circuits each having at least one thin film transistor attached to each other with a resin;

a light emitting element electrically connected to one of the stacked thin film integrated circuits; and

a light receiving element electrically connected to another one of the stacked thin film integrated circuits,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element.

10. (Previously Presented) A semiconductor device comprising:

a plurality of stacked thin film integrated circuits each having at least one thin film transistor attached to each other with a resin;

a metal oxide partially formed on either surface of each of the stacked thin film integrated circuits;

a light emitting element electrically connected to one of the stacked thin film integrated circuits; and

a light receiving element electrically connected to another one of the stacked thin film integrated circuits,

wherein a first electric signal is converted to an optical signal in the light emitting element,

wherein the optical signal is converted to a second electric signal in the light receiving element.

11. (Original) A mobile phone having the semiconductor device according to any one of claims 1 to 10.

12. (Original) An electronic book having the semiconductor device according to any one of claims 1 to 10.

13. (Original) A personal computer having the semiconductor device according to any one of claims 1 to 10.

14. (Previously Presented) An electronic card having the semiconductor device according to any one of claims 1 to 10.

15. (Previously Presented) A watch card having the semiconductor device according to any one of claims 1 to 10.

16. (Previously Presented) A semiconductor device according to any one of claims 1 and 2, wherein the signal from the thin film transistor is inputted to the light emitting element.

17. (Previously Presented) A semiconductor device according to any one of claims 1 and 2, wherein the signal from the light receiving element is inputted to the thin film transistor.

18. (Previously Presented) A semiconductor device according to any one of claims 3 to 10, wherein the first electric signal from the thin film transistor is inputted to the light emitting element.

19. (Previously Presented) A semiconductor device according to any one of claims 3 to 10, wherein the second electric signal from the light receiving element is inputted to the thin film transistor.

20. (New) A semiconductor device according to any one of claims 1 to 10, wherein the light emitting element is an organic light emitting device.

21. (New) A semiconductor device according to any one of claims 1 to 10, wherein the light emitting element comprises a first electrode, a second electrode, and an electro-luminescent layer between the first electrode and the second electrode.